



SPECIFICATIONS

Operating Pressure	4050 PSI
Maximum Pressure	4500 PSI
Maximum Flow	10.5 GPM
Temperature	195°F
Port Sizes:	
Inlet	3/8" BSP-M
Discharge	3/8" BSP-F
Bypass	1/2" BSP-F
Dimensions	3.7" x 1.8" x 6.5"
Weight	2.0 lb.
Material	Brass, Stainless Steel, Buna-N

FEATURES

- Premium pressure compensated unloader for low spike pressures
- Adjustable max pressure settings
- Stainless steel internal components for maximum durability

PARTS LIST

No.	Kit Part No.	Description	Qty.
	Kit*Y60161524	Repair kit	1
1.	Y60181131	3/8 BSP F nipple	1
2.	* Y10306601	O-ring 1.78 x 15.6 mm	2
3.	Y60005351	Spring	1
4.	Y60005251	S.S. check valve	1
5.	* Y10321308	O-ring 3 x 6 mm	1
6.	Y60172535	Valve body	1
7.	* Y60180951	Seat	1
8.	* Y60180851	M8 shutter	1
9.	* Y10306801	O-ring 1.78 x 17.17 mm	1
10.	Y60181031	Spacer	1
11.	* Y60097924	Valve piston seal repair set	1
12.	* Y10307201	O-ring 1.78 x 20.35 mm	1
13.	Y60097331	Piston housing	1
14.	Y16210000	M 4 x 4 mm dowel	1
15.	Y60172831	Lock ring	1
16.	* Y60097824	Piston seal repair set	1
17.	Y60180651	M 8 piston	1
18.	* Y14744310	S.S. 11/32" ball	1
19.	Y60181331	Spring guide	1
20.	Y60097561	4.5 x 47 mm spring	1
21.	Y60172731	Brass cap	1
22.	Y60172684	Black plastic cap	1

